



产品说明书

&\$%

AUhYf]U` HndY DD5Z;:' \$! =	; fUXY BUaY DD5 L*H &% \$! G=
: YUhi fYg	<] [\ hci [\bYgg ; ccX UddYUfUbWV ; ccX ac` X] b[UbX dfcWVgg] b[dYfZcfaUbWV
AUhYf]U` GhUbXUfX	
5j U]` UV]` hm	5g] Ubl DUW]Z] W
DfcWVgg AYh\cX	=b^YVh] cb Ac` X] b[
5ddYUfUbWV	7c` cf g Cdh] cbU`
5dd`] WUh] cbg	5i hcacV]` Y 9` YVh]f] WU] #9` YVh]f]cb] W 5dd`] WUh] cbg

; YbYfU` DfcdYfh] Yg

Bc"	DfcdYfh] Yg	AYh\cXg	I b] hg	JU` i Yg	HYgh 7cbX] h] cbg
%	8Ybg] hm	=GC %%` ! %	[#VhR`	%` ,	&
&	:` ck Ac` X] b[g\`f] b_U[Y	DF9H	!	\$` "	&
'	HfUbgj YfgY Ac` X] b[g\`f] b_U[Y	DF9H	!	\$` -	&
(HYbg]` Y GhfYb[h\ Uh AUl @cUX	=GC)&+! &	ADU	%+\$) \$aa#a] b
)	9` cb[Uh]cb Uh 6fYU_	=GC)&+! &	!	&` \$r` ") \$aa#a] b
*	:` Yl i fU` GhfYb[h\	=GC %+,	ADU	&` \$	&aa#a] b
+	:` Yl i fU` AcXi` l g	=GC %+,	ADU	, \$\$\$	&aa#a] b
,	=adUW` GhfYb[h\	=GC %+-! %	_>#aR&	-\$	&
-	BchWXYX =adUW` GhfYb[h\	=GC %+-! %	_>#aR&	%	&

DfcWVgg] b[Vh]bX] h] cbg

8fm] b[7cbX"	%%\$` !%&\	#%&) !` \
Ac] ghi fY` 7cbhfc`	\$` &	
=b^YVh]cb HYad"	' \$\$!` ' (\$	
Ac` X HYad"	, \$r` %)\$	

注：以上数据为实验典型值，真实可靠，仅作参考，不能认定为材料性能最小值。

Note: The technical data above are authentic and reliable for reference. These value cannot be defined as the minimal performance value.