



产品说明书

&\$%

AUhYf]U` HndY DD5 ;:' \$; fUXY BUaY DD5 L*H &&' \$! : F
: YUhi fYg	<U` c[Yb! ZfYY Z` UaY fYhUFxUbh ; ccX ac` X] b[UbX dfcWgg] b[dYfZcfaUbW <] [\ ghfYb[h\
AUhYf]U` GhUbXUFX	5g] Ub! DUW]Z] W
5j U]` UV]`] hm	=b^YVh] cb Ac` X] b[
DfcWgg AYh\cX	7c` cf g Cdh] cbU`
5ddYUfUbW	5i hcacV]` Y 9 YVh]f] W] #9 YVh]cb] W 5dd`] WU] cbg
5dd`] WU] cbg	

; YbYfU` DfcdYfh] Yg

Bc"	DfcdYfh] Yg	AYh\cXg	I b] hg	JU` i Yg	HYgh 7cbX] h] cbg
%	8Ybg] hm	=GC %%' !%	[#VhR	% ()	&'
&	: `ck Ac` X] b[g\]f] b_U[Y	DF9H AYh\cX		\$"'	&' # (, \
'	HfUbg] YfgY Ac` X] b[g\]f] b_U[Y	DF9H AYh\cX		% \$	&' # (, \
(HYbg]` Y GhfYb[h\ Uh AU] @cUX	=GC) &+! &	ADU	% \$) \$aa#a] b
)	9 cb[U]h] cb Uh 6fYU_	=GC) &+! &		% \$r&')) \$aa#a] b
*	: `YI i fU` GhfYb[h\	=GC %+,	ADU	&&\$	&aa#a] b
+	: `YI i fU` AcXi` i g	=GC %+,	ADU	%\$ \$	&aa#a] b
,	=adUW] GhfYb[h\	=GC %+-! %	_>#a ^a	()	&'
-	BchVXYX =adUW] GhfYb[h\	=GC %+-! %	_>#a ^a	+	&'
%\$: `UaaUV]`] hm	I @ (!	J! \$	\$" (aa
%%	7H=	=97 *\$%&	J	*\$ \$!
%&	<8H	=GC +)! &		&'	% , ADU
%	KUhYf UVgcf dh] cbf]GUi fUh] cbt	=GC * &		(" \$	' aaž&'
%(KUhYf UVgcf dh] cbf]9ei]`] V]f] i at	=GC * &		%)	' aa) \$! F<

DfcWgg] b[WcbX] h] cbg

8fm] b[7cbX"	%)r%&) t*r%& \
Ac] ghi fY 7cbhfc`	\$" &
=b^YVh] cb HYad"	&- \$! ' &\$
Ac` X HYad"	%&\$r%\$

注：以上数据为实验典型值，真实可靠，仅作参考，不能认定为材料性能最小值。

Note: The technical data above are authentic and reliable for reference. These value cannot be defined as the minimal performance value.